



HOW TO APPLY TO CARS, BOATS AND RVs

EXTERIOR and INTERIOR

Prep Product

1. Shake gallon well. Product must be diluted 1:1 with water. For easier handling, pour desired amount into clean, new smaller container, then add water.
2. Shake mixture well.

Prep Surface

1. Thoroughly clean and remove any visible surface contaminants.
2. Clay bar if needed.
3. Do any needed paint correction.

Apply

1. Only work small areas at a time. Dampen microfiber cloth or foam applicator sponge with water.
2. Apply product onto the surface with a vertical and horizontal motion.
3. Dry buff immediately with second microfiber cloth in similar manner until product is completely absorbed.

GLASS AND MIRRORS

Prep Product

1. Dilution rate is 4 parts water to 1 part coating.
2. Pour water into clean, new spray bottle first.
3. Add coating and shake.

Prep Surface

1. Thoroughly clean surface.

Apply

1. Only work small areas at a time. Dampen microfiber cloth or foam applicator sponge with water. Spray mixture to dampened cloth or sponge.
2. Apply product onto the surface with a vertical and horizontal motion.
3. Dry buff immediately with second microfiber cloth in similar manner until product is completely absorbed.

Note: You can spray directly onto surface.
Any overspray must also be dry buffed.